

www.bravapower.com

BRAVA[®]
POWER PRODUCTS

QUALITY
ATTITUDE
BEST



generators



water pumps



EL SAYAD
TRADING MISR

INTERNATIONAL COMMERCIAL
& INDUSTRIAL INVESTMENT (S.A.E.I)

POWERED by **HONDA**

GENERATORS SINGLE PHASE



STANDARD	NAC3100	NAC3100C	NAC5000	NAC7000
GENERATOR	N S M - S A C C A R D O			
AC Frequency	50 Hz	50 Hz	50 Hz	50 Hz
AC Output (V)	220V.	220V.	220V.	220V.
Rated AC Output (KVA)	2.4 KVA	2.4 KVA	3.5 KVA	5 KVA
Max. AC Output (KVA)	2.7 KVA	2.7 KVA	3.9 KVA	5.5 KVA
ENGINE	H O N D A			
Model	GX160	GX160	GX270	GX390
Type / Net Power (Hp / rpm)	4-stroke 5.5 Hp / 3600 rpm	4-stroke 5.5 Hp / 3600 rpm	4-stroke 9 Hp / 3600 rpm	4-stroke 13 Hp / 3600 rpm
Starting System	Recoil	Recoil	Recoil	Recoil
Fuel Tank / Operation time	3.6 Lit / 3 Hrs	15 Lit / 8 Hrs	6 Lit / 3.5 Hrs	6.5 Lit / 3.5 Hrs
Sound Level (dba) at 7 M	68 dbA	68 dbA	68 dbA	69 dbA
DIMENSIONS				
LxWxH (mm)	620 x 400 x 525 mm	620 x 400 x 525 mm	730 x 490 x 523 mm	740 x 490 x 525 mm
Weight (Kg)	42 kgs	43 kgs	60 kgs	73 kgs

GENERATORS SINGLE PHASE



STANDARD	BR7500	BR7500 S	BR8500	BR8500 S
GENERATOR	N S M - S A C C A R D O			
AC Frequency	50 Hz	50 Hz	50 Hz	50 Hz
AC Output (V)	220V.	220V.	220V.	220V.
Rated AC Output (KVA)	6 KVA	6 KVA	7 KVA	7 KVA
Max. AC Output (KVA)	6.5 KVA	6.5 KVA	7.5 KVA	7.5 KVA
ENGINE	H O N D A			
Model	GX390	GX390	GX390	GX390
Type / Net Power (Hp / rpm)	4-stroke 13 Hp / 3600 rpm	4-stroke 13 Hp / 3600 rpm	4-stroke 13 Hp / 3600 rpm	4-stroke 13 Hp / 3600 rpm
Starting System	Recoil	Electric Starter	Recoil	Electric Starter
Fuel Tank / Operation time	25 Lit / 8 Hrs	25 Lit / 8 Hrs	25 Lit / 8 Hrs	25 Lit / 8 Hrs
Sound Level (dba) at 7 M	69 dbA	69 dbA	69 dbA	69 dbA
DIMENSIONS				
LxWxH (mm)	760 x 550 x 740 mm	760 x 550 x 740 mm	760 x 550 x 740 mm	760 x 550 x 740 mm
Weight (Kg)	75 kgs	80 kgs	83 kgs	85 kgs

GENERATORS SINGLE PHASE



STANDARD	BR9500 CS	BR11500 CS	BR15000 CS	BR17000 CS
GENERATOR	N S M - S A C C A R D O			
AC Frequency	50 Hz.	50 Hz.	50 Hz.	50 Hz.
AC Output (V)	220V.	220V.	220V.	220V.
Rated AC Output (KVA)	8 KVA	10 KVA	13 KVA	15 KVA
Max. AC Output (KVA)	8.5 KVA	11 KVA	14 KVA	16 KVA
ENGINE	H O N D A			
Model	GX630	GX630	GX690	GX690
Type / Net Power (Hp / rpm)	4-stroke 21 Hp / 3600 rpm	4-stroke 21 Hp / 3600 rpm	4-stroke 24 Hp / 3600 rpm	4-stroke 24 Hp / 3600 rpm
Starting System	Electric Starter	Electric Starter	Electric Starter	Electric Starter
Fuel Tank / Operation time	25 Lit / 5 Hrs	25 Lit / 5 Hrs	25 Lit / 4.5 Hrs	25 Lit / 4.5 Hrs
Sound Level (dba) at 7 M	71 dbA	71 dbA	72 dbA	72 dbA
DIMENSIONS				
LxWxH (mm)	950 x 700 x 660 mm	950 x 700 x 660 mm	950x700x660 mm	950x700x660 mm
Weight (Kg)	145 kgs	148 kgs	153 kgs	149 kgs

GENERATORS SINGLE PHASE



AVR	BR11500 CSR AVR	BR13500 CSR AVR	BR17000 CSR AVR
GENERATOR	N S M - S A C C A R D O		
AC Frequency	50 Hz.	50 Hz.	50 Hz.
AC Output (V)	220V.	220V.	220V.
Rated AC Output (KVA)	10 KVA	12 KVA	15 KVA
Max. AC Output (KVA)	11 KVA	13KVA	16 KVA
ENGINE	H O N D A		
Model	GX630	GX630	GX690
Type / Net Power (Hp / rpm)	4-stroke 21 Hp / 3600 rpm	4-stroke 21 Hp / 3600 rpm	4-stroke 24 Hp / 3600 rpm
Starting System	Electric Starter	Electric Starter	Electric Starter
Fuel Tank / Operation time	25 Lit / 5 Hrs	25 Lit / 5 Hrs	25 Lit / 4.5 Hrs
Sound Level (dba) at 7 M	71 dbA	72 dbA	72 dbA
DIMENSIONS			
LxWxH (mm)	950 x 700 x 660 mm	950 x 700 x 660 mm	950 x 700 x 660 mm
Weight (Kg)	145 kgs	148 kgs	149 kgs

GENERATORS THREE PHASE



STANDARD	BRT8500	BRT8500 S	BRT13500CS	BRT22000 CS
GENERATOR	N S M - S A C C A R D O			
AC Frequency	50 Hz.	50 Hz.	50 Hz.	50 Hz.
AC Output (V)	380/220V.	380/220V.	380 / 220V.	380 / 220V.
Rated AC Output (KVA)	7/3.3 KVA	7/3.3 KVA	12 / 6 KVA	18 / 9 KVA
Max. AC Output (KVA)	7.5/3.5 KVA	7.5/3.5 KVA	13 / 6 KVA	19/9 KVA
ENGINE	H O N D A			
Model	GX390	GX390	GX630	GX690
Type / Net Power (Hp / rpm)	4-stroke 13 Hp / 3600 rpm	4-stroke 13 Hp / 3600 rpm	4-stroke 21 Hp / 3600 rpm	4-stroke 24 Hp / 3600 rpm
Starting System	Recoil	Electric Starter	Electric Starter	Electric Starter
Fuel Tank / Operation time	25 Lit / 8 Hrs	25 Lit / 8 Hrs	25 Lit / 5 Hrs	25 Lit / 4.5 Hrs
Sound Level (dbA) at 7 M	69 dbA	69 dbA	71 dbA	72 dbA
DIMENSIONS				
LxWxH (mm)	760x550x740 mm	760x550x740 mm	950x700x660 mm	950x700x660 mm
Weight (Kg)	83 kgs	85 kgs	148 kgs	153 kgs

GENERATORS THREE PHASE



AVR	BRT12000 CSR AVR	BRT15500 CSR AVR	BRT16500 CSR AVR	BRT22000 CSR AVR
GENERATOR	N S M - S A C C A R D O			
AC Frequency	50 Hz.	50 Hz.	50 Hz.	50 Hz.
AC Output (V)	380 / 220V.	380 / 220V.	380 / 220V.	380 / 220V.
Rated AC Output (KVA)	10 / 5 KVA	13 / 6.5 KVA	15 / 7.5 KVA	18 / 9 KVA
Max. AC Output (KVA)	11 / 5 KVA	14 / 6.5 KVA	16 / 7.5 KVA	19 / 9 KVA
ENGINE	H O N D A			
Model	GX630	GX690	GX690	GX690
Type / Net Power (Hp / rpm)	4-stroke 21 Hp / 3600 rpm	4-stroke 24 Hp / 3600 rpm	4-stroke 24 Hp / 3600 rpm	4-stroke 24 Hp / 3600 rpm
Starting System	Electric Starter	Electric Starter	Electric Starter	Electric Starter
Fuel Tank / Operation time	25 Lit / 5Hrs	25 Lit / 4.5 Hrs	25 Lit / 4.5 Hrs	25 Lit / 4.5 Hrs
Sound Level (dbA) at 7 M	71 dbA	72 dbA	72 dbA	72 dbA
DIMENSIONS				
LxWxH (mm)	950 x 700 x 660 mm	950 x 700 x 660 mm	950 x 700 x 660 mm	950 x 700 x 660 mm
Weight (Kg)	145 kgs	148 kgs	149 kgs	153 kgs

GENERATORS SILENT



A V R	BR17000 CSR X AVR	BRT22000 CSR X AVR
GENERATOR	NSM - SACCARDO	
AC Frequency	50 Hz	50 Hz
AC Output (V)	220V.	380 / 220V.
Rated AC Output (KVA)	15 KVA	18 / 9 KVA
Max. AC Output (KVA)	16 KVA	19 / 9 KVA
ENGINE	H O N D A	
Model	GX690	GX690
Type / Net Power (Hp / rpm)	4-stroke 24 Hp / 3600 rpm	4-stroke 24 Hp / 3600 rpm
Starting System	Electric Starter	Electric Starter
Fuel Tank / Operation time	25 Lit / 4.5 Hrs	25 Lit / 4.5 Hrs
Sound Level (dbA) at 7 M	65 dbA	65 dbA
DIMENSIONS	H O N D A	
LxWxH (mm)	1200 x 900 x 1000 mm	1200 x 900 x 1000 mm
Weight (Kg)	250 kgs	250 kgs

GENERATORS WELDERS



W E L D E R	BR250AW	BR250AWS
GENERATOR	NSM - SACCARDO	
AC Frequency	50 Hz.	50 Hz.
AC Output (V)	220V.	220V.
Rated AC Output (KVA)	7 KVA	7 KVA
DC Output Welder	200 Amp. 35% / 180 Amp. 60%	200 Amp. 35% / 180 Amp. 60%
Usable Electrodes	Ruttle, Acid 4mm	Ruttle, Acid 4mm
ENGINE	H O N D A	
Model	GX390	GX390
Type / Net Power (Hp / rpm)	13 Hp / 3600 rpm	13 Hp / 3600 rpm
Starting System	Recoil	Electric Starter
Fuel Tank / Operation time	25 Lit / 8 Hrs	25 Lit / 8 Hrs
Sound Level (dbA) at 7 M	70 dbA	70 dbA
DIMENSIONS	H O N D A	
LxWxH (mm)	380 x 550 x 740 mm	380 x 550 x 740 mm
Weight (Kg)	100 kgs	102 kgs

WATER PUMPS



SELF PRIMING PUMP	W20	W30	W40
	A l u m i n u i m C a s e		
Inlet / Outlet Diameter	50 mm (2 inch)	80 mm (3 inch)	100 mm (4 inch)
Total Head	26 m (85.3 ft.)	30 m (98.4 ft.)	30 m (98.4 ft.)
Suction Head	8 m (26.2 ft.)	8 m (26.2 ft.)	8 m (26.2 ft.)
Max. Pumping Capacity	600 Lit. / min	1000 Lit. / min	1600 Lit. / min
Self Priming Time / 5m	90 sec.	120 sec.	120 sec.
	H O N D A		
Model	GX120	GX160	GX270
Type / Net Power (Hp / rpm)	4-stroke 4 Hp / 3600 rpm	4-stroke 5.5 Hp / 3600 rpm	4-stroke 9 Hp / 3600 rpm
Starting System	Recoil	Recoil	Recoil
Fuel Tank / Operation time	2.5 Lit / 3 Hrs	3.6 Lit / 3 Hrs	6.0 Lit / 3.5 Hrs
	D I M E N S I O N S		
LxWxH (mm)	520 x 400 x 400 mm	550 x 440 x 520 mm	640 x 550 x 570 mm
Weight (Kg)	28 kgs	32 kgs	52 kgs

HISTROY OF BRAVA

BRAVA Power Products has been introduced to the markets since 1993 to become one of the leading power products manufacturers in the world. The company offers a variety of generators, water pumps, and construction equipment made of the highest quality components. Through partnering with the pioneers of the industry: Honda Power Products, MSN Saccardo, Leroy Somer, Markon Sawafuji, and others, BRAVA guarantees quality, reliability, innovation and durability. In the heart of Egypt, BRAVA stands tall with a 16,000sqm factory, served by over 150 employees that bring quality assurance to 100% of the factory's production. BRAVA offers you 1 year full warranty, and 24/7 after sales service to maintain the best after sales experience for its clients

QUALITY OF BRAVA

BRAVA Power Products has been introduced to the markets since 1993 to become one of the leading power products manufacturers in the world.
BRAVA is using only Honda genuine engines on all its products.
BRAVA focuses on quality, reliability, innovation, and durability.
BRAVA focuses on after sales service, customers satisfaction.
BRAVA uses high quality components on all its machineries.

OUR PARTNERS



109 Omar Ebn El Khattab St. Almaza,
 Heliopolis, Cairo - Egypt.
 Tel: 00202 24143321 - 24143393
 Fax: 00202 22909782
 Mail: info@elsayad.com.eg
 www.bravapower.com